

GA25HR

2.5kW output, 120V, Honda

The GA25HR model is ideal for small tool applications and with its high quality construction; this unit is tough enough for any jobsite condition.

- Lightweight and compact design for easy transport
- 100% copper windings for maximum conductivity
- Alternator design eliminates maintenance by removing brushes and slip rings
- Hour meter for proper service intervals and usage information
- Heavy-duty 1-inch (25 mm) steel pipe frame and shock mounts protect the generator
- Runs for six hours on a full tank at full load
- Powered by a Honda GX160 engine with low-oil shutdown



Unit Specifications

Alternator Design	Brushless	
Frequency	60 hz	
Phase	Single Phase	
Voltage	120 V	
Sound level at 30 ft	70 dBA	
Fuel Tank Capacity	3.2 gal	12 L

Power Generation

	Maximum	Continuous
Watts	2500 W	2200 W
Amps at 120V	20.8 A	18.3 A
Amps at 240V	0 A	0 A

Receptacles & Circuit Breakers

Main Circuit Breaker	20 A	
Number of Poles	1	
1 Receptacle of Each:	5-20R 125V GFCI 20A L5-20R 125V T-Lock 20A	

Dimensions & Weights

Overall Length	20.9 in	530 mm
Overall Width	17.7 in	450 mm
Overall Height	20.1 in	510 mm
Shipping Dimensions	20.9 x 17.7 x 20.1 in 530 x 450 x 510 mm	
Operating Weight	132 lb	60 kg
Shipping Weight	110 lb	50 kg

Engine Specifications

Engine Make/Model	Honda GX-160	
Start Method	Recoil	
Engine Power	5.5 HP	4.1 kW
Engine RPM	3600	
Fuel Type	Gasoline	

Notice: Features and equipment specifications are subject to change without notice.