

GA36HR

3.6kW, 120/240V, Honda

An all-around performer that delivers 120/240V output in a mid-size package. This unit is ideal for supplying power to heaters, power tools and small air-compressors. HR models come standard with a GFCI protected main breaker, hour meter, wheel kit and automatic idle control.

- Lightweight and compact design for easy transport
- 100% copper windings for maximum conductivity
- Alternator design eliminates maintenance by removing brushes and slip rings
- Heavy-duty 1-inch (25 mm) steel pipe frame and shock mounts protect the generator
- Includes a wheel kit and folding lifting bale as standard equipment
- Powered by Honda GX240 engine with low-oil shutdown and idle control
- Full panel GFCI protection - OSHA and NEC compliant



Unit Specifications

Alternator Design	Brushless	
Frequency	60 hz	
Phase	Single Phase	
Voltage	120/240 V	
Sound level at 30 ft	76 dBA	
Fuel Tank Capacity	5 gal	19 L

Power Generation

	Maximum	Continuous
Watts	3600 W	3200 W
Amps at 120V	30 A	26.6 A
Amps at 240V	15 A	13.3 A

Receptacles & Circuit Breakers

Main Circuit Breaker	21 A	
Number of Poles	2	
1 Receptacle of Each:	L5-20R 125V T-Lock 20A L5-30R 125V T-Lock 30A L14-20R 125/250V T-Lock 20A	
2 Receptacle of Each:	5-20R 125V GFCI 20A	

Dimensions & Weights

Overall Length	25.5 in	64 mm
Overall Width	22 in	56 mm
Overall Height	24 in	61 mm
Operating Weight	215.73 lb	97.85 kg
Shipping Weight	174 lb	79 kg

Engine Specifications

Engine Make/Model	Honda GX-240 (Recoil Only)	
Start Method	Recoil	
Engine Power	7.1 HP	5.3 kW
Engine RPM	3600	
Fuel Type	Gasoline	

Notice: Features and equipment specifications are subject to change without notice.