

MLT

Light tower trailer, less power source

The base unit for the MLT-series light towers. Offered without a power source for contractors who already own a Multiquip DA7000 generator or SDW225SS welder. It can also be used to provide lighting for indoor applications by connecting directly to an alternate power source.

- Can be used with a Multiquip DA7000SS generator or SDW225SS welder
- Withstands winds up to 72 mph (115 kph) with, and 55 mph (88 kph) without, an approved generator
- Ballasts and light switches are protected by inside a waterproof box
- Mast extends to 30 feet (9 meters) and can be rotated 360 degrees
- Four 1,000-watt metal halide floodlights illuminates an area of 5 to 7 acres (3.2 hectares)

Unit Specifications

Sound Level @ 23ft		0 dBA
Fuel Tank Capacity	0 gal	0 L
Ground Clearance	6.5 in	165 cm
Standard Hitch Type	29228 — 2" Ball Adjustable	
Optional Hitch Types	29369 — 3" Pintle	

Lighting Specifications

Floodlights	4 — 1000 watt Metal Halide	
Light Coverage	5 to 7 acres acres	
	2 to 2.8 hectares hectares	
Lumens	440,000	
Lamp Termination	4 x 3-pin QD Plug	

Tower Specifications

Max. Tower Height	32 ft	9.75 m
Tower Support Points	4	
Wind Stability w/ Genset	72 mph	116 kph
Wind Stability w/o Genset	45 mph	72 kph
Winch Capacity	1,500 lb	680.4 kg
Winch Wire Size	3/16 in	

Generator Specifications

Max. Generator Output	W
Cont. Generator Output	W
Voltage	V
Amperage	A
Receptacles	

Welder Specifications

Max. Amperage	A
Current Range	W
Voltage Range	V
Duty Cycle	@ 200A

Notice: Features and equipment specifications are subject to change without notice.