



System made of Aluminum

Pressure adjustable: 3 - 123 PSI (0.2 - 8 bars)
 Abrasive Range: 30-350 Mesh (2.5 - 0.025 mm)
 Hose length: 30 ft. (10 m)
 Standard nozzle size: 13/32" (10 mm)
 Tank capacity: 10.5 gal. / 1.4 ft³ / 84 lbs (40 liter)
 Usage Rate: 2-3 lbs./sq. ft. avg.
 Performance: 75-150 sq. ft./h avg.
 System height (w/out handle): 29"
 System width (w/out front legs): 18" (w/legs 14")
 Packaging (box) dimensions: 21x25x37"
 Machine net weight (empty tank): 98~ lbs.
 Cleaning surfaces: steel, aluminum, stainless steel, wood, glass, marble, concrete, masonry, stone, composite materials, etc.

IBIX 25 H2O System, including:
 13/32" Nozzle (10 mm) Standard
 30 ft. hose
 Application Gun and Water nozzle
 Filling Funnel w/Sieve

ASME compliant # 41,780



IBIX 9 Nozzle Kit



Water nozzle




Adjustable Flow



Lance Extension

AIR CONSUMPTION AT NOZZLE (measured in cubic feet/minute = cfm):

Nozzle	Pressure					IBIX Compressor Option: IBIX VRK520D Requires 185 CFM
	58 PSI (4 bar)	72.5 PSI (5 bar)	87 PSI (6 bar)	101.5 PSI (7 bar)	116 PSI (8 bar)	
Standard 13/32"	139 cfm	153 cfm	167 cfm	183 cfm	195 cfm	
<i>Also available for this system:</i>						
Size 9/32"	80 cfm	88 cfm	95 cfm	101 cfm	107 cfm	
Size 5/16"	90 cfm	98 cfm	107 cfm	117 cfm	125 cfm	
Size 15/32"	200 cfm	220 cfm	240 cfm	264 cfm	280 cfm	

Informational Chart according to ISO 5167

Abrasives:

IBIX ART STRONG: 30-40 Mesh
 IBIX ART SPEED BLAST: 60 Mesh
 IBIX ART MEDIUM: 80 Mesh
 IBIX ART FINE: 120-150 Mesh
 IBIX ART EXTRA FINE: 200-350 Mesh
 IBIX CARBON ART Z5: ~0.212 = ~212 μm
 IBIX CARBON ART Z6: ~0.106 = ~106 μm

**DUST FREE
 BLASTING:**
 Wet Nozzle
 Or
 For Dry blasting
 Vacuum Attachment

