



System made of Aluminum

- Pressure adjustable:** 3 - 130 PSI (0.2 - 9 bars)
- Abrasive Range: 20-350 Mesh (2.5 - 0.025 mm)
- Hose length: 20 ft. (6 m)
- Standard nozzle size: 1/8" (3 mm)
- Tank capacity: 2.4 gal. / 0.32 ft³ / 19.2 lbs (9 liter)
- Usage Rate: 0.75-1.5 lbs./sq. ft. avg.
- Performance: 35-55 sq. ft./h avg.
- System height (w/out handle): 25"
- System width (w/out front legs): 8" (w/legs 14")
- Packaging (box) dimensions: 14x17x31"
- Machine net weight (empty tank): ~35 lbs.
- Cleaning surfaces: steel, aluminum, stainless steel, wood, glass, marble, concrete, masonry, stone, composite materials, etc.

IBIX 9 H2O System, including:
1/8" Nozzle (3 mm) Standard
20 ft. hose
Application Gun and Water nozzle
Filling Funnel w/Sieve



IBIX 9 Nozzle Kit




VORTEX Technology



Adjustable Flow

ASME compliant # 41,780

AIR CONSUMPTION AT NOZZLE (measured in cubic feet/minute = cfm):

Nozzle	Pressure					IBIX Compressor Options: IBIX US 8422 Gas Compressor
	58 PSI (4 bar)	72.5 PSI (5 bar)	87 PSI (6 bar)	101.5 PSI (7 bar)	116 PSI (8 bar)	
Standard 1/8"	13 cfm	14.5 cfm	15.5 cfm	16.7 cfm	17.7 cfm	
<i>Also available for this system:</i>						
Size 3/32"	9 cfm	10 cfm	10.8 cfm	11.5 cfm	12.3 cfm	
Size 5/32"	23.2 cfm	25.6 cfm	27.8 cfm	29.8 cfm	31.6 cfm	

Informational Chart according to ISO 5167



DUST FREE
BLASTING:
Wet Nozzle
Or
For Dry blasting
Vacuum Attachment



Abrasives:

- IBIX ART STRONG: 30-40 Mesh
- IBIX ART SPEED BLAST: 60 Mesh
- IBIX ART MEDIUM: 80 Mesh
- IBIX ART FINE: 120-150 Mesh
- IBIX ART EXTRA FINE: 200-350 Mesh
- IBIX CARBON ART Z5: ~0.212 = ~212 µm
- IBIX CARBON ART Z6: ~0.106 = ~106 µm



Surface Technologies

IBIX Systems designed for MULTIPLE GREEN ABRASIVES (Garnet, Calcium, Glass, Walnut, and other)